

# 5 MEGAPIXEL CLOUD MICRO DOME CAMERA

\_ S1505



The **S1505** is a cloud managed IP camera with 5 megapixel resolution and built-in edge recording. The camera records video 24x7 to on-board storage eliminating the cost of an external NVR. With advanced video analytics for person and vehicle detection and superb low-light capability, it is the most compact all-in-one surveillance solution on the market. A single cable for data and power-over-Ethernet (PoE) makes it easy to install. The S1505 does not require any additional hardware or software on site for operation. Viewing, playback and camera configuration can be done through the KastleVideo Cloud VMS using just a web browser or mobile app. The camera supports cloud video backup as well as integration with VMS and alarm monitoring platforms for added peace-of-mind.

## **CAMERA**



#### **ADVANCED VIDEO ANALYTICS**

Detection and classification of people, vehicles, and loitering. Advanced clutter rejection dramatically reduces false alarms by up to 85% compared to outdoor PIRs or cameras with motion detection.



# LOW-LIGHT AND DAY/NIGHT SWITCHING

Exceptional low-light performance with a Sony Starvis<sup>TM\*</sup> sensor and multi-element glass lens. The camera automatically switches to night mode to allow ambient IR light for enhanced monitoring in dark scenes.



#### **BUILT-IN DVR**

Built-in 24/7 edge recording for 30 days at 1.5MP or 10 days at 5MP. Eliminating the need for a separate external NVR.





#### **CLOUD FEDERATION**

All cameras across multiple locations are federated into a single unified system that scales from one camera to thousands of cameras. This drastically reduces system cost and complexity.



#### WEB AND MOBILE VIEWING

Use a web browser to log into the cloud VMS and view live, playback recorded video or use our advanced search engine to find video in seconds. Our mobile apps also put this capability within easy reach.



#### CYBER-SECURITY INCLUDED

Hacker-proof and secure using 2048 bit certificates. Built-in firewall and encrypted communication for added security.







### **5 MEGAPIXEL CLOUD MICRO DOME CAMERA** model S1505

CAMERA

0.15 lux **Image Sensor** Minimum 1/2.8" Progressive CMOS Illumination Color

**Effective Pixels** 2592x1944(5MP) 2.8 mm focal length/F 1.6 Lens

**VIDEO** 

Resolutions 2592 x 1944(5MP)/1440x1080 H.264/H.265 Main Profile Video

(1.5MP)Compression

VIDEO MANAGEMENT

Works with KastleVideo Cloud **Central Station** Hosted Bold Manitou, Micro Key Software Automation VMS. Offers 100% web and MKMS, SIMS II/III, Immix®,

Software mobile viewing, AI search and SGS-stages Integration cloud backup. No NVR needed

on-site.

**ANALYTICS** 

**Engine** Person Detection, 10 to 60 feet Auto-calibrating analytics with **Analytics** 

tracking and classification engine Vehicle Detection, 30 to 75 feet

for people and vehicles. Zone Violation Rejects clutter from environment Loitering Person and illumination changes. Stopped Vehicle

Video Alarm 10-second video clip generated

upon trigger of alarm; contains 2-4 seconds of pre-alarm video

**NETWORK** 

**Protocols** Wired IPv4/v6, TCP/IP, UDP, HTTP, 10/100Mbps Ethernet (RJ-45)

HTTPS, IGMP, DHCP, RTP/RTSP, HTTPS, IP Filter, TLS 1.2 Security

HLS

5W

**DVR** 

Web Player Resolutions 5MP or 1.5MP Live streaming compatible

with web browsers and mobile Recording

Built-in 24/7 edge recording devices

for 30 days at 1.5MP or 10

**GENERAL** 

**Power Source Dimensions** Ø 116 x 56 mm (Ø 4.56 x 2.20 PoE 802.3af

in.)

days at 5MP

**Power** 

Operating -20°C ~ 55°C (-4°F ~ 131° F) Consumption Conditions

Humidity: 10% ~ 90%, no **Approvals** CE, FCC, NDAA Compliant condensation

> Part Number 201696

